

SPECIFICATIONS:

**MATERIALS:**






HOUSING: PBT, UL94 V-0  
 CONTACTS: GOLD FLASH PLATED BRASS  
 SHELL: TIN PLATED STEEL

**ELECTRICAL:**

RATED CURRENT: 5A  
 WORKING VOLTAGE: 250V  
 INSULATION RESISTANCE: 1000 MOhms MIN.  
 CONTACT RESISTANCE: 15 mOhms MAX.

**ENVIRONMENT:**

OPERATING TEMPERATURE: -55°C TO +105°C



25-PIN FEMALE	25-PIN FEMALE
1 - - - - - 1	1
2 - - - - - 2	2
3 - - - - - 3	3
24 - - - - - 24	24
25 - - - - - 25	25
SHELL - - - - SHELL	

RoHS COMPLIANT

UNITS = inch [mm]

DO NOT SCALE FROM DRAWING



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN:  
C. SMITH

DATE:  
10/12/2007

NorComp

SCALE: NTS	SHEET 1	OF 1	REV 4
---------------	------------	---------	----------

DWG NO. GCLP25F25F