

## SPECIFICATIONS:

## MATERIALS:

HOUSING:

PA66, UL94 V-0, BLACK

CONTACTS:

GOLD FLASH PLATED BRASS

## ELECTRICAL:

RATED CURRENT:

SEE TABLE TO LEFT

250V

RATED VOLTAGE:

100 MOhms MIN.

INSULATION RESISTANCE:




10 mOhms MAX.

CONTACT RESISTANCE:

## POSITIONS AVAILABLE

NorComp Part Number	POSITIONS (MATING VIEW)	MAX AMPERAGE	MAX WIRE AWG
868-02A-103R001	2A	10A	18AWG
868-03A-103R001	3A	10A	18AWG
868-04A-103R001	4A	10A	18AWG
868-02B-103R001	2B	5A	24AWG
868-03B-103R001	3B	5A	24AWG
868-04B-103R001	4B	5A	24AWG
868-005-103R001	5	5A	24AWG
868-006-103R001	6	5A	24AWG
868-007-103R001	7	5A	24AWG
868-008-103R001	8	5A	24AWG


NOTE: 2A, 3A, & 4A MUST MATE WITH CORRESPONDING A SIZES  
 2B, 3B, & 4B MUST MATE WITH CORRESPONDING B SIZES



## ENVIRONMENT:

OPERATING TEMPERATURE: -40°C TO +105°C

IP67



UNITS = mm

DO NOT SCALE FROM DRAWING



THESE DRAWINGS AND SPECIFICATIONS ARE  
 THE PROPERTY OF NorComp AND SHALL NOT  
 BE REPRODUCED, COPIED OR USED AS THE  
 BASIS FOR THE MANUFACTURE OR SALE OF  
 APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN:  
 J. KADEL

DATE:  
 01/12/2026

NorComp

SCALE: NTS SHEET 1 OF 1 REV 0

DWG NO. 868-YYY-103R001