


SPECIFICATIONS:

MATERIALS:	
HOUSING:	PBT, UL94 V-0, BLACK
CONTACTS:	10µ" GOLD PLATED BRASS
NUT:	NICKEL PLATED ALUMINUM ALLOY
SHELL:	NICKEL PLATED ALUMINUM ALLOY
MAIN BODY:	NICKEL PLATED ALUMINUM ALLOY
GLAND:	SILICONE, BLACK
GLAND CAGE:	POM, WHITE
GLAND NUT:	NICKEL PLATED ALUMINUM ALLOY
ORING:	SILICONE

ELECTRICAL:	
RATED CURRENT:	1.5A
RATED VOLTAGE:	30V
INSULATION RESISTANCE:	100 MOhms MIN.
CONTACT RESISTANCE:	10 mOhms MAX.

ENVIRONMENT:	
OPERATING TEMPERATURE:	-40°C TO +85°C
WATER PROOF:	IP67

MAX WIRE AWG:	26 AWG
---------------	--------



RoHS COMPLIANT



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN:	J. KADEL
DATE:	12/11/2023

UNITS = mm

DO NOT SCALE FROM DRAWING

NorComp	SCALE:	SHEET	OF	REV
	NTS	1	1	0
DWG NO.		858-017-103RKT4		