

DESCRIPTION: M12 // F // 17P ACODE // SOLDER CUP // CABLE MOUNT // UNSHIELDED

SPECIFICATIONS:

MATERIALS:

HOUSING: PBT, UL94 V-0, BLACK  
CONTACTS: 10µ" GOLD PLATED BRASS  
NUT: NICKEL PLATED BRASS  
ORING: EPDM




ELECTRICAL:

RATED CURRENT: 1.5A  
RATED VOLTAGE: 30V  
INSULATION RESISTANCE: 100 MOhms MIN.  
CONTACT RESISTANCE: 10 mOhms MAX.


ENVIRONMENT:

OPERATING TEMPERATURE: -40°C TO +85°C  
WATER PROOF: IP67

MAX WIRE AWG: 26 AWG



NUT



RoHS COMPLIANT



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN:  
J. KADEL

DATE:  
12/11/2023

UNITS = mm

DO NOT SCALE FROM DRAWING

NorComp

SCALE:  
NTS

SHEET 1 OF 1

REV 0

DWG NO.

858-017-203RSU4