


NOTE:

MATERIAL
HOUSING: PBT UL94V-0, BLACK
CONTACT: 10µ" GOLD PLATED BRASS
SHELL: SEE P/N KEY
NUT: SEE P/N KEY
O-RING: EPDM, BLACK

ELECTRICAL
RATED CURRENT: 4A
RATED VOLTAGE: 250V
INSULATION RESISTANCE: 100 MΩhms MIN.
CONTACT RESISTANCE: 10 mΩhms MAX.
WATER PROOF: IP67

ENVIRONMENT
OPERATION TEMPERATURE: -40°C TO +85°C



858-B05-10YRLSY

3 = BRASS/TIN SHELL & BRASS/NICKEL NUT
S = STAINLESS STEEL SHELL & NUT

1 = GOLD FLASH
4 = 10µ" GOLD

RoHS COMPLIANT



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN: J. KADEL
DATE: 11/10/2021

UNITS = mm DO NOT SCALE FROM DRAWING

SCALE: NTS	SHEET 1 OF 1	REV 1
DWG NO. 858-B05-10YRLSY		