



SPECIFICATIONS:

MATERIALS:	
HOUSING:	PA66, UL94 V-0, BLACK
CONTACTS:	10u" GOLD PLATED BRASS
NUT:	NICKEL PLATED BRASS
ORING:	EPDM

ELECTRICAL:	
RATED CURRENT:	12A
RATED VOLTAGE:	63V
INSULATION RESISTANCE:	100 MOhms MIN.
CONTACT RESISTANCE:	10 mOhms MAX.

ENVIRONMENT:	
OPERATING TEMPERATURE:	-40°C TO +105°C
WATER PROOF:	IP67

MAX WIRE AWG:	16 AWG MAX
---------------	------------



NUT

RoHS COMPLIANT

DRAWN:	J. KADEL
DATE:	02/15/2023

UNITS = mm

DO NOT SCALE FROM DRAWING



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

NorComp

SCALE:	NTS	SHEET	OF	REV
		1	1	1
DWG NO.	858-T04-203RLU4			