



NOTE:

MATERIAL

HOUSING:
CONTACT:
SHELL
NUT:
O-RING:

PBT UL94V-0, BLACK
BRASS
BRASS
BRASS
EPDM, BLACK

FINISH

CONTACT:

10u" GOLD PLATED
OVER 50u" NICKEL

SHELL:
NUT

NICKEL PLATED OVER ALL
NICKEL PLATED OVER ALL

ELECTRICAL:

RATED CURRENT:
RATED VOLTAGE:
INSULATION RESISTANCE:
CONTACT RESISTANCE:
WATER PROOF:

4A
250V
100 MΩhms MIN.
10 mΩhms MAX.
IP67

ENVIRONMENT:

OPERATION TEMPERATURE:

-40°C TO +85°C

RoHS COMPLIANT



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN:

J. KADEL

DATE:

07/24/2020

UNITS = mm

DO NOT SCALE FROM DRAWING

NorComp

SCALE:

NTS

SHEET

1

OF

1

REV

0

DWG NO.

859-004-103R0M4