

						<u>,C,D LHIDOI</u>	
Rohs Compliant			UNITS = mm) NOT SC	ALE FRO	om draw	ING
M	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE	DRAWN: J. KADEL	NorCom	SCALE: NTS	SHEET C	F 1	REV 0
R.	BARLENKOBOLED, COFIED ON COSED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DATE: 05/14/2025	NorComp	^{DWG NO.} 860-D04-113RST4			





DESCRIPTION: M12 // M // 4P // DCODE // PCB VERT // REAR PANEL MOUNT


15.0

10.8

 \bigcirc

 \bigcirc

 \bigcirc



SPECIFICATIONS:

MATERIALS:

PBT, UL94 V-0, BLACK
10u" GOLD PLATED BRASS
NICKEL PLATED BRASS
NICKEL PLATED BRASS
EPDM, BLACK

ELECTRICAL:

RATED CURRENT: 4A 250V RATED VOLTAGE: INSULATION RESISTANCE: 100 MOhms MIN. CONTACT RESISTANCE: 10 mOhms MAX.

ENVIRONMENT:

OPERATING TEMPERATURE: -40°C TO +85°C WATER PROOF: IP67

