



NOTE:

MATERIAL	
M12 INSULATOR	PA66, UL94V-0, BLACK
SPLITTER HOUSING	PVC, UL94V-0, BLACK
CONTACT	GOLD FLASH PLATED BRASS
NUT	NICKEL PLATED BRASS
ELECTRICAL	
RATED CURRENT	2A(8P) / 4A(4/5P)
VOLTAGE	30V(8P) / 60V(5P) / 250V(4P)
INSULATOR RESISTANCE	100 MOhms MIN.
CONTACT RESISTANCE	10 mOhms MAX.
MATING CYCLES	100 CYCLES MIN
ENVIRONMENT	
OPERATION TEMPERATURE	-40°C TO +85°C
IP RATING	IP67 (UNCOUPLED & COUPLED)
RECOMMENDED TORQUE	0.4Nm TO 0.8Nm

FEMALE

A04	A05	A08	D04	B05

Y58-YYY-FFF001

SERIES	Y58 = M12 Y-SPLIT ADAPTER
CONTACT ARRANGEMENT	A04 = (3X) 4P A-CODE A05 = (3X) 5P A-CODE A08 = (3X) 8P A-CODE D04 = (3X) 4P D-CODE B05 = (3X) 5P B-CODE
GENDER	FFF = FEMALE / FEMALE / FEMALE
CONTACT PLATING	1 = GOLD FLASH

RoHS COMPLIANT



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN: J. KADEL
DATE: 12/20/2021

TOLERANCES
.x ±0.5
.xx ±0.2
ANGULAR ±1°

UNITS = mm DO NOT SCALE FROM DRAWING

NorComp	SCALE: NTS	SHEET 1 OF 1	REV 3
	DWG NO. Y58-YYY-FFF001		