



DESCRIPTION: M16 // M // SOLDER CUP // FRONT PANEL MOUNT // SHIELDED









SPECIFICATIONS:

MATERIALS:

HOUSING:PA66, UL94 V-0, BLACKCONTACTS:GOLD FLASH PLATED BRASSNUT:NICKEL PLATED BRASSSHELL:NICKEL PLATED BRASSORING:EPDM

ELECTRICAL:

RATED CURRENT: RATED VOLTAGE: INSULATION RESISTANCE: CONTACT RESISTANCE: 7A (3,4,5B) // 5A (6,7A,7B,8) 250V 100 MOhms MIN. 10 mOhms MAX.

ENVIRONMENT:

OPERATING TEMPERATURE: -40°C TO +85°C WATER PROOF: IP67

MAX WIRE AWG:


TORQUE:

22 AWG

0.7Nm to 1.5Nm

879-YYY-103RF01

POSITIONS (SEE POSITION CHART) 003 = 3 POSITION 004 = 4 POSITION 05B = 5(B) POSITION 006 = 6 POSITION 07A = 7(A) POSITION 07B = 7(B) POSITION 008 = 8 POSITION



POSITION CHART (MATING SIDE SHOWN)

RoHS C	OMPLIANT		UNITS = mm	o not sc	ale from draw	/ING
K	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWN: J. KADEL	NorComp	SCALE: NTS	SHEET OF 1 1	REV 3
		DATE: 09/05/2023	Νοισοιή	DWG NO.	879-YYY-103RF01	