

MATERIALS AND FINISH:

PBT THERMOPLASTIC 30% GLASS FILLED

UL 94V-0 RATED, BLACK COLOR

3 AMPS


10 mOHMS Max. 1,000VAC Min.

5 GOHMS Min.

-55° ~ +125° C

DIMENSIONS (in.)						
No. OF PINS	Α	В	С	D		
15	0.642	0.984	1.213	0.090		
26	0.969	1.311	1.543	0.090		
44	1.512	1.852	2.089	0.090		
62	2.157	2.500	2.732	0.095		

DIMENSIONS (mm)						
No. OF PINS	Α	В	С	D		
15	16.30	25.00	30.80	2.29		
26	24.60	33.30	39.20	2.29		
44	38.40	47.05	53.05	2.29		
62	54.80	63.50	69.40	2.41		



DO NOT SCALE FROM DRAWING

BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DESCRIPTION: HIGH DENSITY - MACHINED CONTACTS - SOLDER CUP

DATE:


03/13/2007

NorComp


OF REV 19 2 DWG NO. 180-MYY-20YLYYY

ALL CLINCH-NUTS ARE 4-40 INTERNAL THREADS


01X 0.098" (SOLDER SIDE)



02X 0.236" (SOLDER SIDE)



03X..... 0.236" (MATING SIDE)





DRAWN: C. SMITH DATE: 03/13/2007

DO NOT SCALE FROM DRAWING SCALE: NTS

SHEET

2 2

19

REV

180-MYY-20YLYYY