

SPECIFICATIONS:

ELECTRICAL:

INSULATION RESISTANCE: 1,000 MOhms MIN. **OPERATING TEMPERATURE:** -50°C TO +100°C VOI TAGE:

500 VAC FOR 1 MINUTE

MATERIALS:

INSULATOR: PBT +30% GF, UL94 V-0

PROCESS TEMP:


SHELL: NICKEL PLATED STEEL

COMPATIBLE WITH NORCOMP CONTACT PART NUMBERS BELOW:

180-002-170L001 180-102-170L001

NOTE: CONTACTS MUST BE PURCHASED SEPARATELY

230°C



BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DATE: 07/19/2005 UNITS = inch [mm]

DO NOT SCALE FROM DRAWING

SCALE: SHEET NTS

OF 1

REV

22

DWG NO.

180-YYY-27YLYY0


NorComp

TOLERANCE:

ALL DIMENSIONS ARE ±0.010


ALL CLINCH-NUTS ARE 4-40 INTERNAL THREADS


02 0.250" (SOLDER SIDE)



0.200 [5.10] -

01 0.157" (SOLDER SIDE)





03 0.250" (MATING SIDE)

Rohs Compliant

例

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION

DRAWN:
P. JENKINS

DATE: 07/19/2005

UNITS = inch [mm]

NorComp

DO NOT SCALE FROM DRAWING

SCALE:
NTS
DWG NO.

SHEET 2

OF 2 2

2

REV

22

180-YYY-27YLYY0