




DESCRIPTION: R/A .318" FILTERED D-SUB



	A	B	C	D
9	1.204	.984	.480	.433
	30.6	25.0	12.20	10.99
15	1.535	1.312	.480	.757
	39.0	33.3	12.20	19.23
25	2.078	1.850	.480	1.305
	52.8	47.0	12.20	33.15
37	2.724	2.500	.480	1.957
	69.2	63.5	12.20	49.71



479-YYY-212RYY1

SERIES _____
POSITIONS _____
009
015
025
037
050
GENDER _____
1 = MALE
2 = FEMALE
TERMINATION _____
1 - DIP SOLDER
SHELL PLATING _____
2 = TIN
HARDWARE OPTIONS _____
00 = NO HARDWARE
58 = STABILIZER BAR(4-40 INSERT/BRDLOCK)
PLATING OPTIONS _____
1 = GOLD FLASH

SPECIFICATIONS:
MATERIALS:
SHELL: STEEL, TIN PLATED
INSULATOR: UL 94V-0 RATED PBTP
GLASS-FIBER REINFORCED
ELECTRICALS:
INDIVIDUAL CAPACITOR VALUE = 1000 pF
OTHER VALUES AVAILABLE: CONSULT FACTORY
CURRENT RATING: 5 AMPS
CONTACT RESISTANCE: <10 mOHMS
INSULTOR RESISTANCE: 1000 OHMS
VOLTAGE: 1 KV / AC
TEMPERATURE: -55°C TO +125°C

RoHS COMPLIANT

	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OF SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWN: WAYNE ROBBINS		DATE: 9-06-98		
		CHECKED:		DATE:		
NorComp			SCALE: 1:1	SHEET 1	OF 1	REV 0
			DWG NO. 479-YYY-212RYY1			