



NOTE:

MATERIAL

HOUSING  
FLANGE  
CONTACT  
SHELL  
O-RING  
SEALING COMPOUND  
HARDWARE

PBT UL94V-0, BLACK  
PBT UL94V-0, BLACK  
BRASS, PLATING P/N KEY BELOW  
STEEL, NICKEL  
SILICONE  
EPOXY  
BRASS; NICKEL PLATED

ELECTRICAL

SIGNAL CONTACT RATED CURRENT  
POWER CONTACT RATED CURRENT  
VOLTAGE  
INSULATOR RESISTANCE  
SIGNAL CONTACT RESISTANCE  
POWER CONTACT RESISTANCE  
WATER PROOF

5A  
P/N KEY BELOW  
1000 VAC 1 MIN  
5 GOhms MIN.  
10 mOhms MAX.  
2.0 mOhms MAX.  
IP67

ENVIRONMENT

OPERATION TEMPERATURE

-25°C TO +85°C

SERIES CDFS11W1103LYYY  
CDF = COMBO DSUB FLANGE  
CONTACT TYPE S = SOLDER CUP  
POSITION 11W1  
GENDER 2 = FEMALE  
POWER CONTACT AMPERAGE 2 = 20 AMPS  
4 = 40 AMPS  
HARDWARE OPTIONS 1 = 4-40 THREADED INSERTS/4-40 JACKSCREWS  
CONTACT PLATING OPTIONS 1 = GOLD FLASH  
2 = 30u" GOLD PLATING

RoHS COMPLIANT



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN:  
J. KADEL  
DATE:  
06/08/2020

TOLERANCES  
X. ±0.40  
.X ±0.30  
.XX ±0.20  
.XXX ±0.10

UNITS = mm

DO NOT SCALE FROM DRAWING

NorComp

SCALE:  
NTS

SHEET 1 OF 1

REV 1

DWG NO.

CDFS11W1203LYYY