
DESCRIPTION: DSUB IP67 FLANGE // FEMALE // COMBO // VERTICAL PIN PCB MOUNT



2.0 m0hms MAX. IP67 -25°C TO +85°C CDFV13W3213LYYY CDF = COMBO DSUB FLANGEV = VERTICAL PCB MOUNT

PBT UL94V-0, BLACK

PBT UL94V-0, BLACK

BRASS; NICKEL PLATED

STEEL, NICKEL

P/N KEY BELOW

1000 VAC 1 MIN

10 m0hms MAX.

5 GOhms MIN.

SILICONE

EPOXY


5A

BRASS, PLATING P/N KEY BELOW


7.90±0.30 7.90±0.30	<u></u>		(2PCS)	$\begin{array}{rcl} & 4-40 & \\ & & $				
RoHS (GOMPLIANT		TOLERANCES	UNITS = mm	do not sc	GALE FR	30m Drav	WING
К.	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWN: J. KADEL DATE: 04/27/2020	X. ±0.40 X. ±0.30 XX ±0.20 XXX ±0.20	NorCom	D SCALE: NTS DWG NO.	SHEET 1 CDFV13	^{of} 2 3W3213LY	REV 1 YY

**Ø3.20MM HOLES NOT NEEDED FOR "1" HARDWARE OPTION

20 AMP CONFIGURATION



40 AMP CONFIGURATION



RECOMMENDED PCB LAYOUT *TYPICAL // HOLE SIZE MAY NOT BE SUITABLE FOR YOUR SPECIFIC APPLICATION

