

DESCRIPTION: MALE - HIGH DENSITY - MACHINED CONTACTS - SOLDER CUP






MATERIALS AND FINISH:

SHELL: INSULATOR:	STEEL MATERIAL, NICKEL FINISH PBT THERMOPLASTIC 30% GLASS FILLED UL 94 V-0 RATED, BLACK			
CONTACT MATERIAL: CONTACT FINISH: SEALING MATERIAL:	(PROCESS TEMP 230°C) BRASS SELECTIVE GOLD FINISHED F08 FLEXIBLE ADHESIVE			

ELECTRICAL:


CONTACT CURRENT RATING:	3 AMPS
CONTACT RESISTANCE:	30 mOHMS Max.
DIELECTRIC WITHSTANDING VOLTAGE:	1,000VAC Min.
INSULATION RESISTANCE:	5 GOHMS Min.
TEMPERATURE RATING:	-55° ~ +105° C

	DIMENSIONS				
No. OF PINS	А	В	С	D	
15	1.213	0.984	0.666	0.759	
26	1.541	1.312	0.994	1.083	
44	2.088	1.852	1.534	1.625	






RoHS COMPLIANT DO NOT SCALE FROM DRAWING UNITS = inch DRAWN: REV THESE DRAWINGS AND SPECIFICATIONS ARE C. SMITH **NorComp** THE PROPERTY OF NorComp AND SHALL NOT NTS 3 6 1 BE REPRODUCED, COPIED OR USED AS THE DWG NO. DATE: BASIS FOR THE MANUFACTURE OR SALE OF 780-MYY-103LYY1 06/11/2009 APPARATUS WITHOUT WRITTEN PERMISSION.





ALL CLINCH-NUTS ARE 4-40 INTERNAL THREADS

01X 0.098" (SOLDER SIDE)



RoHS C	OMPLIANT		UNI	TS = inch [mm]	NOT SC/	ALE FROM	n Drawi	ING
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWN: C. SMITH		NorComp	SCALE: NTS	SHEET OF	3	REV 6	
	ANUFACTURE OR SALE OF DATE:	NorComp	DWG NO.	780-MYY-1	03LYY1			







RoHS C	FOMPLIANT			DO) NOT SCI	ALE FR(om draw	71NG
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF	DRAWN: C. SMITH	NorComp	SCALE: NTS	SHEET 3	OF 3	REV 6		
BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DATE: 06/11/2009		NorComp	DWG NO.	780-MY\	(-103LYY1		