



MAX. PANEL THICKNESS WILL BE DEPENDANT ON WHAT
HARDWARE IS USED // MAXIMUM DISTANCE BETWEEN FLANGE
MATING FACES OF MATING CONNECTORS IS 0.216 in [5.49 mm]*
*IF USING NORCOMP'S 960 BACK SHELL KIT THE 0.216 in
DESIGNATION ABOVE DOES NOT APPLY

REAR MOUNTED*

	A	B	C
9 POSITION	0.565 [14.35]	0.410 [10.41]	0.256 [6.50]
15 POSITION	0.715 [18.16]	0.560 [14.22]	0.256 [6.50]
25 POSITION	0.965 [24.51]	0.810 [20.57]	0.256 [6.50]

TOLERANCE = +0.010/-0.000 inch

NOTES:

*THESE DIMENSIONS ARE RECOMMENDED BUT MAY NOT SUIT ALL APPLICATIONS
IF YOU HAVE ANY QUESTIONS REGARDING THESE DIMENSIONS PLEASE REACH OUT TO ENG@NORCOMP.NET

**DIMENSIONS ABOVE ONLY TO BE USED WITH 380 & 381 SERIES MICRO D CONNECTORS

RoHS COMPLIANT

UNITS = inch[mm]

DO NOT SCALE FROM DRAWING



THESE DRAWINGS AND SPECIFICATIONS ARE
THE PROPERTY OF NorComp AND SHALL NOT
BE REPRODUCED, COPIED OR USED AS THE
BASIS FOR THE MANUFACTURE OR SALE OF
APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN:

J. KADEL

DATE:

04/02/2020

NorComp

SCALE:

NTS

SHEET

1

OF

1

REV

2

DWG NO.

Panel_Cutout_Micro-D